

WHAT IS CLAIMED IS

5

1. A method of generating a free-form surface model, comprising the steps of:

applying linear transformation to a lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model; and

generating control points of cubic Bezier curves that connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model.

20

2. The method as claimed in claim 1, further comprising a step of interpolating Gregory patches into a mesh comprised of the cubic Bezier curves.

25

00912034600

Sub 1

3. The method as claimed in claim 1, further comprising a step of adding rounding information to the lattice polygon model, the rounding information controlling how round the free-form surface model is
5 when the free-form surface model is generated from the lattice polygon model and the rounding information, wherein said step of applying linear transformation includes a step of generating the vertices of the free-form surface model by utilizing the rounding information.

10

4. The method as claimed in claim 3, wherein
15 said rounding information includes rounding information attached to the vertices and the edges of the lattice polygon model.

20

5. The method as claimed in claim 1, further comprising a step of reconstructing the lattice polygon model from the free-form surface model by utilizing an
25 inverse transformation of the linear transformation.

00950-85560

6. A computer-readable memory medium having a program embodied therein for causing a computer to generate a free-form surface model, said program comprising program code units configured to perform the steps of:

applying linear transformation to a lattice polygon model to generate vertices of a free-form surface model corresponding to respective vertices of the lattice polygon model; and

generating control points of cubic Bezier curves that connect the vertices of the free-form surface model, and that correspond to respective edges of the lattice polygon model.

15

7. The computer-readable memory medium as claimed in claim 6, further comprising a step of interpolating Gregory patches into a mesh comprised of the cubic Bezier curves.

25

00970-03100
SUBA

8. The computer-readable memory medium as claimed in claim 6, further comprising a step of adding rounding information to the lattice polygon model, the rounding information controlling how round the free-form surface model is when the free-form surface model is generated from the lattice polygon model and the rounding information, wherein said step of applying linear transformation includes a step of generating the vertices of the free-form surface model by utilizing the rounding information.

9. The computer-readable memory medium as claimed in claim 8, wherein said rounding information includes rounding information attached to the vertices and the edges of the lattice polygon model.

10. The computer-readable memory medium as claimed in claim 6, further comprising a step of reconstructing the lattice polygon model from the free-

00910-03400

Sub 41

form surface model by utilizing an inverse transformation of the linear transformation.

5

11. A method of transmitting 3D data via a network, comprising the steps of:

adding rounding information to a lattice
10 polygon model, the rounding information controlling how
round a free-form surface model is when the free-form
surface model is generated from the lattice polygon
model and the rounding information by applying linear
transformation to the lattice polygon model to generate
15 vertices of the free-form surface model corresponding to
respective vertices of the lattice polygon model, and
generating control points of cubic Bezier curves that
connect the vertices of the free-form surface model, and
that correspond to respective edges of the lattice
20 polygon model; and

transmitting the lattice polygon model and the
rounding information over the network.

25

005558-031500

```

    receiving a lattice polygon model and rounding
5  information via a network;

```

10 generating control points of cubic Bezier
curves that serve as edges to connect the vertices of
the free-form surface model, and that correspond to
respective edges of the lattice polygon model, wherein
the rounding information controls how close the vertices
15 and edges of the free-form surface model are to the
respective vertices and edges of the lattice polygon
model.

13. A server device for transmitting 3D data
via a network, configured to add rounding information to
a lattice polygon model, the rounding information
controlling how round a free-form surface model is when

5
10

20

25

information controls how close the vertices and edges of the free-form surface model are to the respective vertices and edges of the lattice polygon model.

5

09525558.031500